

Face Construction	IMPERIAL	METRIC
Construction	Tufted Patterned Textured Loop	
Tufted Pile Weight	22.0 oz/sq yd	746 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	12.0 stitches / inch	47.2 stitches/10 cm
Finished Pile Height	0.157 inch	4.0 mm
	0.079 inch	2.0 mm
Total Finished Weight	60.21 oz/sq yd	2041.1 g/sq m
Kilotex	11.9	
Fiber System	Dyex SD® nylon	
Dye Method	Solution Dyed	
Pattern Repeat	12.0" W x 16.67" L	304.80 mm W x 423.42 mm L
Soil Protection	ENSURE	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm

### Color Line

01271 Shiitake	01276 Stainless
01272 Haystack	01277 Moonstone
01273 Woodbark	01278 Carbon
01274 Tamari	01279 Lacquer
01275 Obi	

### Product Testing/Information

IAQ Results	CCI/CRI Green Label Plus Registration Number GLP9878. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class I (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

### Warranties

5 Year Limited Colourfastness (Atmospheric Fumes)
10 Year Limited Colourfastness (Light)
10 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kV)
10 Year Limited No Delamination or Edge Ravel

### Product Notes

All specifications are subject to normal manufacturing tolerances.  
Dyelot may vary from samples.  
The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.  
Crossley Carpet Mills Limited reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

### Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.  
To achieve best results, more time should be allowed to install patterned carpet. This styles has a definite pattern and must be installed according to pattern match procedures as outlined in Crossley Carpet Mills Limited installation specifications, available from your Tandus Representative.  
Manufacturing tolerances on Crossley tufted carpets are:  
Bow - 3/4" per 12' width  
Skew - 1" per 12' width  
Edge Straightness - +/- 1/2" variation  
Pattern Elongation - 1 1/4" per 12' length  
For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.  
Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.  
Recommendations are available from your Tandus Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at [www.tandus.com/limitedwarranty](http://www.tandus.com/limitedwarranty) and [www.tandus.com/maintenance](http://www.tandus.com/maintenance) or by dialing 800-248-2878.

Crossley Carpet Mills Limited, A Tandus® Company

435 Willow Street PO Box 745 Truro, Nova Scotia B2N 5G2 T 800.248.2878 [tandus.com](http://tandus.com)