

Face Construction	IMPERIAL	METRIC
Construction	Tufted Textured Loop	
Tufted Pile Weight	28 oz/sq yd	949 g/sq m
Gauge	1/10 inch	39.4 rows/10 cm
Stitches per Inch	9.8 stitches / inch	38.6 stitches/10 cm
Finished Pile Height	0.197 inch	5.0 mm
	0.117 inch	3.0 mm
Total Finished Weight	66.21 oz/sq yd	2245 g/sq m
Kilotex	12.8	
Fiber System	Antron® Legacy nylon	
Dye Method	Piece Dyed	
Pattern Repeat	N/A	
Soil Protection	ENSURE	
Backing Construction	Super-Lok® enriched latex backing	
Width	12 feet	366 cm

Color Line

01685 Pebble	03388 Vapor	04632 Teazle	04692 Night Sky	08564 Brown Bear
01695 Sunfish	03398 Mica	04642 Forest	05241 Wildfire	09419 Bittersweet
01705 Goldenrod	03408 Carbonite	04652 New Shoot	05251 Canyon Copper	09529 Oak Leaf
01715 Wild Joney	03917 Cavern	04662 Moss	08534 Riverbed	
02413 Mountain Stream	03927 Beach Plum	04672 Pine Needle	08544 Smoke	
02423 Slate	04622 Lichen	04682 Hummingbird	08554 Shadow	

Product Testing/Information

IAQ Results	CCI/CRI Green Label Plus Registration Number GLP2478. (Low VOC emitter.)			
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70		
	Flooring Radiant Panel	ASTM E-648 Class I (Direct Gluedown)		
	Smoke Density	ASTM E-662 Less than 450		
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD		

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

Warranties

- 10 Year Limited Abrasive Wear
- Lifetime Limited Anti-Static (Less than 3.5 kV)
- 10 Year Limited No Delamination or Edge Ravel

Product Notes

All specifications are subject to normal manufacturing tolerances.
Dyelot may vary from samples.

The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Crossley Carpet Mills Limited reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Antron® Legacy nylon has been certified by Scientific Certification Systems as an Environmentally Preferable Product.

Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.

To achieve best results, more time should be allowed to install patterned carpet. This styles has a definite pattern and must be installed according to pattern match procedures as outlined in Crossley Carpet Mills Limited installation specifications, available from your Tandus Representative.

Manufacturing tolerances on Crossley tufted carpets are:

- Bow - 3/4" per 12' width
- Skew - 1" per 12' width
- Edge Straightness - +/- 1/2" variation
- Pattern Elongation - 1 1/4" per 12' length

For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.

Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.

Recommendations are available from your Tandus Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at www.tandus.com/limitedwarranty and www.tandus.com/maintenance or by dialing 800-248-2878.

Crossley Carpet Mills Limited, A Tandus® Company

435 Willow Street PO Box 745 Truro, Nova Scotia B2N 5G2 T 800.248.2878 tandus.com